STILO-BL

Hydraulic hole punching tool



Hydraulic head made of high-strength material

FLEXIBLE

Head swiveling and rotatable by 360 °

AUTOMATIC RETURN

At the end of the punching cycle

ERGONOMIC

Fatigue-free working and easy handling thanks to a balanced 2-component handle

POWERFUL

18V lithium-ion battery 1.5Ah for even more punching with one battery power

INTELLIGENT

Multifunction LED to indicate the maintenance intervals (10.000 cycles)

intercable.com

INTERCABLE GmbH Rienzfeldstrasse, 21 I-39031 Bruneck info@intercable.com

intercable

Technical Characteristics

Suitable for punching round, square and rectangular holes up to max. 3 mm material thickness.


Characteristics:

- · Light, compact and robust construction
- Ergonomic 2-component handle allows fatigue-free working
- Head swiveling / rotating around 360 °
- Fast feed through 3-fold axial piston pump
- Pressure monitoring by electronic pressure sensor
- Fast tool returns through patented return valve
- Manual return possible in any position
- Punch detection, automatic return after releasing from the start switch at the completed punching cycle or by reaching the maximum force.
- · Powerful Li-ion battery
- Fall arrester by means of a hand strap
- Application Temperature range: -10 $^{\circ}$ C / + 40 $^{\circ}.$

Punch perfomance (max. sheet thicknesses):

- Max Ø63,5 mm:.....3,0 mm St-Material/2,5 mm VA-Material
 Max 68,0 x 68,0 mm:....3,0 mm St-Material/1,5 mm VA-Material
- Max 92,0 x 92,0 mm:.....2,5 mm St-Material/1,5 mm VA-Material
- Bigger than 92,0 x 92,0 mm till 138,0 x 138,0 mm 2 mm St-Material

Hydraulic force	60 kN
Head rotation	360°
Operating Pressure	680 bar
Battery voltage	18 V
Weight (with battery)	ca. 2,3 kg
Device dimensions loose with battery	398 x 126 x 82 mm





Description	order no.	dimensions	weight
Hydraulic hole punching tool	STILO-BL	560 x 357 x 120 mm	5,5 kg

Set of equipment & accessories

- Hydraulic cordless puncher Stilo BL
- Battery 18V-1.5Ah (2.0Ah) Li-Ion
- Battery charger (LG8)
- Robust plastic case for holding the Tool, spare battery, charger and hole inserts
- 1x Draw stud 9,5 x 19,0 mm
- 1x Draw stud 19.0 x 125.0 mm
- 1x Distance socket
- 1x Tube anti-wear paste
- HSS Multi step drill for pre-drilling
- USB cable
- CD-ROM (Software)
- \bullet Operating instructions, safety and maintenance instructions

STILO-BL SET

Optional

• 230V AC mains adapter (NG3)



intercable.com

